



SAFETY DATA SHEET

SECTION 1.0	PRODUCT AND COMPANY IDENTIFICATION
--------------------	---

Product Identifier

UNIPAR® D 60 ST

Recommended use (identified)

Industrial Solvent, Functional Fluid, Process Fluid

Uses advised against

Do not use for any purpose other than the one for which it is intended.

Manufacturer/Importer/Supplier/Distributor InformationUNISOURCE-ENERGY, LLC
40 Shuman Blvd, Suite 290
Naperville, IL 60563**E-mail**

orders@unisource-energy.com

Telephone number

Phone: 630-470-6030 Fax: 630-470-6031

Emergency telephone numberUNISOURCE-ENERGY, LLC
1-800-444-5510CHEMTREC
1-800-424-9300

SECTION 2.0	HAZARD(S) IDENTIFICATION
--------------------	---------------------------------

OSHA/HCS statusFlammable liquids – Category 4
Aspiration toxicity -- Category 1**GHS label elements****Signal word**

DANGER



SAFETY DATA SHEET

Hazard statement

Combustible liquid
May be fatal if swallowed and enters airways

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Wear protective gloves/protective clothing/eye protection/face protection

Ingestion

If SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical or foam for extinction

Storage

Store locked up
Store in well ventilated place. Keep cool.

Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown Acute Toxicity

No information available

Hazard(s) not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

Other information

Vapors may form explosive mixtures with air.
The material can accumulate static charge and can therefore cause electrical ignition.

SECTION 3.0

COMPOSITION/INFORMATION ON INGREDIENTS


Chemical name

A complex and variable combination of paraffinic and cyclic hydrocarbons having a carbon number range of C₁₁ to C₁₄ and a boiling range of approximately 180°C to 270°C
The aromatic content is < 2%

CAS number/other identifiers

Ingredient Name	%	CAS No.
Hydrocarbons, C ₁₁ to C ₁₄ , n-alkanes, Isoalkanes, cyclics, < 2% aromatics*	100	*

*Related CAS: 64742-47-8



SAFETY DATA SHEET

SECTION 4.0	FIRST AID MEASURES
--------------------	---------------------------

Description of necessary first aid measures

General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE

Eye contact

Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.

Inhalation

In case of exposure to intense concentrations of vapors, fumes or spray, transport the person away from the contaminated zone, keep warm and allow to rest.

Skin contact

Remove contaminated clothing and shoes. Wash off with soap and water.

Ingestion

Do not ingest. If swallowed, do not induce vomiting - seek medical advice.

Risk of product entering the lungs on vomiting after ingestion. In this case, the casualty should be sent immediately to hospital.

Protection of First Aiders

Use personnel protective equipment

Most important symptoms/effects, acute and delayed

Skin contact

Non-irritating during normal use.

Eye contact

Burning feeling and temporary redness

Inhalation

Vapors inhaled in strong concentration have a narcotic effect on the central nervous system.

Ingestion


If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious pulmonary lesions (medical survey during 48 hours)

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea

Indication of immediate medical attention and special treatment , if necessary

Note to physician

Treat symptomatically



SAFETY DATA SHEET

SECTION 5.0	FIRE-FIGHTING MEASURES
--------------------	-------------------------------

Suitable extinguishing media

Foam, Dry powder. Carbon dioxide (CO₂), Water spray

Uniform Fire Code

Combustible Liquid III-A

Blasting Agents

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Special Hazard

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

Explosion Data

Sensitivity to Mechanical Impact – None

Sensitivity to Static Discharge -- May be ignited by friction, heat, sparks or flames.

Special protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand. MISHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

SECTION 6.0	ACCIDENTAL RELEASE MEASURES
--------------------	------------------------------------

Personal precautions, protective equipment and emergency procedures

General Information

Use personal protective equipment

Evacuate non-essential personnel

Ensure adequate ventilation, especially in confined areas

ELIMINATE all ignition sources (no smoking, fires, sparks or flames in immediate area)

Do not touch or walk through spilled material

Other information


Remove all sources of ignition

Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames.

Environmental precautions

General Information

Prevent further leakage or spillage if safe to do so. Dike to collect liquid spills. The product should not be allowed to enter drains, water courses or the soil. Local authorities should be



SAFETY DATA SHEET

advised if significant spillages cannot be contained. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for clean up

Use non-sparking hand tools and explosion proof electrical equipment.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Following product recovery, flush area with water

SECTION 7.0

HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

For personal protection see Section 8. Avoid contact with skin, eyes and clothing. Use only in well ventilated areas. Do not breathe vapors or spray mist.

Technical measures

Ensure adequate ventilation.

Do not spray at high pressure (> 3 bar) unless a full risk assessment has been carried out and suitable protection measures put in place.

WHILE MOVING THE PRODUCT: To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Do not allow splash loading and ensure that the product is poured slowly, particularly at the beginning of the operation

Prevention of fire and explosion

OPERATE ONLY ON COLD AND DEGASSED TANKS IN VENTILATED PREMISES (TO AVOID RISK OF EXPLOSION).

Handle away from any source of ignition (open flame and sparks) and heat (hot manifolds or casings). Do not smoke.

Use explosion proof electrical equipment. Take precautionary measures against static discharges. Do not use compressed air for filling, discharging or handling.


Design installations (machinery and equipment) to prevent burning product from spreading (tanks, retention systems, interceptors (traps) in drainage systems).

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke.

Regular cleaning of equipment, work area and clothing is recommended. Do not dry hands with rags that have been contaminated with product. Do not use abrasives, solvents or fuels.

Wash hands before breaks and at the end of workday.



SAFETY DATA SHEET

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts.

Storage installations should be designed with adequate bunds so as to prevent ground or water pollution in case of leaks or spills.

Keep in a bunded area. Keep in a dry, cool and well-ventilated place.

Keep away from open flames, hot surfaces and sources of ignition. Ground/bond containers, tanks and transfer/receiving equipment. Store at room temperature.

Keep containers tightly closed and properly labelled.

Packaging material

Keep only in the original container or in a suitable container for this kind of product, steel stainless steel

Materials to avoid

Strong acids, Oxidizing agents

SECTION 8.0	EXPOSURE CONTROLS/PERSONAL PROTECTION
--------------------	--

Control Parameters

Exposure Limits

Contains no substances with occupational exposure limit values

Advisory OEL

CEFIC-HSPA : 1200 mg/m³

Exposure controls

Engineering Measures

When working in confined areas (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear recommended equipment.

Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

General information

Protective engineering solutions should be implemented and in use before personal equipment is considered. These recommendations apply to the product as supplied. If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers.

Eye/Face protection

If splashes are likely to occur, wear safety glasses with side shields

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots.

Hand protection

Protective gloves



SAFETY DATA SHEET

Respiratory protection

If exposure limits are exceeded or irritation is experienced. NIOSH/MAHA approved respiratory protection should be worn. Positive pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current regulations.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke.

Regular cleaning of equipment, work area and clothing is recommended. Do not dry hands with rags that have been contaminated with product. Do not use abrasives, solvents or fuels.

Wash hands before breaks and at the end of workday

SECTION 9.0	PHYSICAL AND CHEMICAL PROPERTIES
--------------------	---

Physical state @ 20°C	Liquid
Color	Colorless
Odor	Petroleum solvent
Odor threshold	No information available
pH	Not applicable
Melting point	No information available
Initial boiling point and boiling range	196 –239°C (385 – 462°F) ISO 3405
Flash point	72°C (162°F) ASTM D 93
Evaporation rate, EtEt = 1	550 DIN 53170
Upper explosive (flammable) limits	6 %
Lower explosive (flammable) limits	0.6 %
Vapor pressure	0.19 hPa @ 20°C
Vapor density	No information available
Relative density	No information available
Density	817 kg/m ³ @ 15°C ISO 12185
Water Solubility	Not applicable
Solubility in other solvents	No information available
LogP_{ow}	Not applicable
Auto-ignition temperature	>230°C (>446°F) ASTM E 659-78
Decomposition temperature	No information available
Viscosity, kinematic	2.1 mm ² /s @ 25°C ASTM D 445
Explosive properties	Not considered explosive based on chemical structure and oxygen balance considerations.
Oxidizing properties	Not applicable. This product is not considered oxidizing based on chemical structure considerations.



SAFETY DATA SHEET

Possibility of hazardous reactions	Not applicable
Surface tension	0.0258 N/m @ 25°C EN 14370
Freezing point	No information available

SECTION 10.0	STABILITY AND REACTIVITY
---------------------	---------------------------------

Reactivity

No information available

Chemical stability

Stable under recommended storage conditions

Possibility of hazardous reactions

None under normal processing

Conditions to avoid

Heat, flames and sparks. Take precautionary measures against static discharges.

Incompatible materials

Strong acids. Oxidizing agents

Hazardous decomposition products

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot,

SECTION 11.0	TOXICOLOGICAL INFORMATION
---------------------	----------------------------------

Acute toxicity**Information on likely routes of exposure****Skin contact**

Non-irritating during normal use.

Eye contact


Burning feeling and temporary redness

Inhalation

Vapors inhaled in strong concentration have a narcotic effect on the central nervous system.

Ingestion

If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious pulmonary lesions (medical survey during 48 hours). Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.



SAFETY DATA SHEET

Numerical measures of toxicity

Product information

ATEmix (oral)	5001 mg/kg
ATEmix (dermal)	5001 mg/kg
ATEmix (inhalation-dust/mist)	5.3 mg/l

Component Information

Hydrocarbons, C ₁₁ to C ₁₄ , n-alkanes, Isoalkanes, cyclics, < 2% aromatics			
Measurement	Species	Results	Method
LC ₅₀ Oral	Rat	>5000 mg/kg bw	OECD 401
LD ₅₀ (24 hr.) Dermal	Rabbit	>5000 mg.kg bw	OECD 402
LC ₅₀ (8 hr. inhalation)	Rat	>5000 mg/m ³ (vapor)	OECD 403

Delayed and immediate effects as well as chronic effects from short and long term exposure

Skin corrosion/irritation

Not classified

Serious eye damage/eye irritation

Not classified

Sensitization

The current toxicological knowledge allows to not classify the product as a sensitizer.

Carcinogenicity

The current toxicological knowledge allows to not classify the product as a carcinogenic.

Mutagenicity

The current toxicological knowledge allows to not classify the product as a mutagenic.

Reproductive toxicity

The current toxicological knowledge allows to not classify the product as a toxic to reproduction

Target Organ Effects (STOT)

None known

Specific Target Organ Toxicity (STOT) - single exposure

None under normal use conditions

Specific Target Organ Toxicity (STOT) – repeated exposure

None under normal use conditions.

Aspiration hazard

May be fatal if swallowed and enters airways



SAFETY DATA SHEET

SECTION 12.0	ECOLOGICAL INFORMATION
---------------------	-------------------------------

Ecotoxicity

Acute aquatic toxicity – Product Information

No experimental data available

Acute aquatic toxicity – Component information

Hydrocarbons, C ₁₁ to C ₁₄ , n-alkanes, Isoalkanes, cyclics, < 2% aromatics			
Measurement	Species	Results	Method
ErL ₅₀ (72 hr.) Algae	Pseudokirchneriella subcapitata	>1000 mg/l	OECD 201
EbL ₅₀ (72 hr.) Algae	Pseudokirchneriella subcapitata	>1000 mg/l	OECD 201
LL ₅₀ (96 hr.) Fish	Oncorhynchus mykiss	>1000 mg/l	OECD 203
EL ₅₀ (48 hr.)	Daphnia magna	>1000 mg/l	OECD 202

Chronic aquatic toxicity – Product information

No experimental data available

Chronic aquatic toxicity – Component information

Hydrocarbons, C ₁₁ to C ₁₄ , n-alkanes, Isoalkanes, cyclics, < 2% aromatics			
Measurement	Species	Results	Method
NOELR (72 hr.) Algae	Pseudokirchneriella subcapitata - biomass	1000 mg/l	OECD 201
NOELR (72 hr.) Algae	Pseudokirchneriella subcapitata – growth rate	1000 mg/l	OECD 201
NOELR (21d) Daphnia	Daphnia magna	1.22 mg/l	QSAR Petrotox
NOELR (28d) Fish	Oncorhynchus mykiss	0.17 mg/l	QSAR Petrotox

Effects on terrestrial organisms

No information available

Persistence and degradability

General Information

Readily biodegradable (69% after 28 days) OECD 301F

Bioaccumulative potential

Product information


Measured experimental data on hydrocarbon UVCB substances are not meaningful, since each of the constituents is likely to behave differently.

LogP_{ow}

Not applicable

Component information

Not applicable



SAFETY DATA SHEET

Mobility in soil

Substance is a UVCB. Standard tests for this endpoint are not appropriate.

General Information

No information available

SECTION 13.0

DISPOSAL CONSIDERATIONS

Waste treatment

Waste disposal methods

Dispose of in accordance with local regulations..

Contaminated packaging

Empty containers may contain flammable or explosive vapors. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14.0

TRANSPORT INFORMATION

DOT

Not regulated

ICAO/IATA

Not regulated

IMDG/IMO

Not regulated

TDG

Not regulated

MEX


Not regulated

ADR (Agreement on Dangerous Goods by Road (Europe))

Not regulated

RID (Regulations Concerning The International Transport of Dangerous Goods (Europe))

Not regulated



SAFETY DATA SHEET

ADN (European Agreement Concerning the International Carriage of Dangerous Goods By Inland Waterways)

Proper shipping name

Substances with a flash-point above 60 degrees C and not more than 100°C

Hazard Class

9

Description

UN9003, SUBSTANCES WITH A FLASH-POINT ABOVE 60 DEGREES C AND NOT MORE THAN 100 DEGREES C (Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics) , 9

SECTION 15.0

REGULATORY INFORMATION

Related CAS Number

64742-47-8

US Federal regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act Section 112 Hazardous Air Pollutants (HAPs) (see 40CFR61)


This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

TSCA

Listed



SAFETY DATA SHEET

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

State Right to Know Laws



No information available

International inventories

Europe	EINECS/ELINCS/NLP	Listed or exempt
Canada	DSL/NDSL	Listed or exempt
Australia	AICS	Listed or exempt
Korea	KECL	Listed or exempt
China	IECSC	Listed or exempt
Japan	ENCS	Listed or exempt
Philippines	PICCS	Listed or exempt
New Zealand	NZIoC	Listed or exempt

SECTION 16.0

OTHER INFORMATION



Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Abbreviations

ACGIH = American Conference of Governmental Industrial Hygienists; ADR = European Road Transport; AICS = Australia Inventory of Chemical Substances; ASTM = American society of Testing and Materials; ATE = Acute Toxicity Estimation; AU = Australia; Autoignition Temperature = The minimum temperature required to initiate combustion in air with no other source of ignition, BCF = Bioconcentration Factor; BEI = - Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent




SAFETY DATA SHEET

as a worker with inhalation exposure to the TLV, BEL = Biological exposure limits; BOD = Biochemical Oxygen Demand; BTEX = Benzene, Toluene, Ethylbenzene, Xylenes; bw = body weight; bw/day = body weight/day; C = Celsius, CA = Canada, CAS = Chemical Abstracts Service; CEFIC = European Chemical Industry Council; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; CLP = Classification Packaging and Labelling Regulation (Regulation (EU) No. 1272/2008; COC = Cleveland Open Cup; CN = China; CPR= Controlled Products Regulations; CWA = Clean Water Act; DEA – Drug Enforcement Administration; DFG = Deutsche Forschungsgemeinschaft; DIN = Deutsches Institut für Normung; DMEL = Derived Minimal Effect Level; DNEL = Derived No Effect Level; DOT = Department of Transportation; DSL = Domestic Substances List (Canada); dw = dry weight; EC = European Commission; EC50 = Effective Concentration fifty; ECC = European Economic Community; ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals; ECHA = European Chemicals Agency; EINECS - European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EL50 = Effective Loading fifty; ENCS = Japan Existing and New Chemical Substances; EPA = Environmental Protection Agency; EU = European Union; EUH statement = CLP –specific Hazard statement; EWC = European Waste Code; F = Fahrenheit; Flash Point = Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air; fw = fresh water; GHS = Globally Harmonized System of Classification and Labelling of Chemicals; GLP = Good Laboratory Practice; HAPs = Hazardous Air Pollutants; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; IBC = Intermediate Bulk Container; IC₅₀ = Inhibitory Concentration fifty; ICAO = International Civil Aviation Organization; IDL = Ingredient Disclosure List; IDLH = Immediately Dangerous to Life and Health; IL₅₀ = Inhibitory Level fifty; IMDG = International Maritime Dangerous Goods; INSHS = National Institute for Health and Safety at Work; INV = Chinese Chemicals Inventory; IOPC = International Oil Pollution Compensation; IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables; JP – Japan; , Kow = Octanol/water partition; KECI = Korea Existing Chemicals Inventory, LC₅₀ = Lethal Concentration (gases) which kills 50% of the exposed animals, LD₅₀ = :Lethal Dose (solids & liquids) which kills 50% of the exposed animals; . LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading; LL₅₀ = Lethal Loading fifty; LEL = The lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.; LogPow = logarithm of the octanol/water partition coefficient; LOLI = List of Lists™ - ChemADVISOR's Regulatory Database; LRT = Lower Respiratory Tract, MARPOL 73/78 = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution; MAK = Maximum Concentration Value in the Workplace; MEL = Maximum Exposure Limits; mg/m³ = : Concentration expressed in weight of substance per volume of air, mg/kg = Quantity of material, by weight, administered to a test subject, based on their body weight in kg, mw = marine water; NDSL = Non-Domestic Substances List (Canada); NE = Not Established; NFPA = National Fire Protection Association; NIOSH = National Institute for Occupational Safety and Health; NJTSR = New Jersey Trade Secret Registry; NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level; NTP = National Toxicology Program; NZ = New Zealand; OECD = Organization for Economic Co-operation and Development; OE-HPV = Occupational Exposure - High Production Volume; or = occasional release; OSHA = U.S. Occupational Safety and Health Administration; PAH = Polycyclic Aromatic Hydrocarbon; PBT = Persistent, Bioaccumulative and Toxic; PEL = Permissible Exposure Limit (OSHA); PH= Philippines; PICCS = Philippines Inventory of Chemicals and Chemical Substances; ppm = Concentration expressed in parts of material per million parts of air or water, PMCC = Pensky Martin Closed Cup; PNEC = Predicted No Effect Concentration; RCRA = Resource Conservation and Recovery; REACH = Registration Evaluation And Authorization Of Chemicals; RID = European Rail Transport; RRN = REACH Registration Number: RQ = Reportable Quantity; RTECS = Registry of Toxic Effects of Chemical Substances®; RTK = Right To Know; SARA = Superfund Amendments and Reauthorization Act; S* = Skin notation; SKIN_DES = Skin Designation; STEL = Short Term Exposure Limit (15 minutes); SCBA = Self-Contained Breathing Apparatus; SDWA = Safe Drinking Water Act; STOT = Specific Target Organ Toxicity, TDLo, = the lowest dose to cause a symptom, TSCA = Toxic Substance Control Act; TCLo = the lowest concentration to cause a symptom; TDo, LDLo, and LDo, or TC, TCo, LCLo, and LCo, the lowest dose (or concentration) to cause lethal or toxic effects, TDG = Transportation of Dangerous Goods; TLV = Threshold Limit Value (ACGIH); TRA = Targeted Risk Assessment; TSCA = Toxic Substances Control Act ; TWA = Time Weighted Average (8 hours); UEL = The highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.; UN = United Nations; URT + Upper Respiratory Track, US = United States; UVCB = Unknown, of Variable Composition, or of Biological Origin; vPvB = very Persistent and very Bioaccumulative; WHMIS = Worker Hazardous Materials Information System (Canada)

Disclaimer

The information presented herein has been compiled from sources considered to be dependable and is accurate as of the date of preparation of this Safety Data Sheet. However, Seller does not assume any liability whatsoever for the accuracy or



SAFETY DATA SHEET

completeness of the information contained herein. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license. All materials may present unknown hazards and should be used with caution. In addition, no responsibility can be assumed by the Seller for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the material. Seller assumes no responsibility for injury to Buyer or to third persons or any damage to any property. Buyer assumes all such risks.